GREASE HYDRAULIC SAFETY COUPLER “Meclube-Lock”

Art. 014-1087-032

Quick coupler Meclube-Lock
With hardened 4-jaws made of tool steel
With high performance hydraulic-gasket
Uncoupling over 600 bar is possible
Swivelling joint with thread M 10x1 mm
Coupler lenght 32 mm
Supplied in blister packaging



014-1087-032

Art. 014-1087-081


Quick coupler Meclube-Lock-L
With hardened 4-jaws made of tool steel
With high performance hydraulic-gasket
Uncoupling over 600 bar is possible
Swivelling joint with thread M 10x1 mm
Coupler lenght 81 mm
Supplied in blister packaging



014-1087-081

THE ADVANTAGES OF THE Meclube-Lock COUPLER

1. Simple activation
To activate the coupler you only have to press the lever with the thumb and insert it on the grease gun.
The hardened 4-jaws maintain the coupler firmly inserted.



2. Simple release
After you have finished the greasing process, you have to press the lever with the thumb to pull out the coupler from the grease gun.



3. Free hands
Once you have activated the coupler, it remains firmly inserted so there is no need to keep it fixed. Its extreme stability allows you to complete the operation with free hands.



4. Universality
Its special design allows to use it with all the grease guns configurations: SAE, DIN, BS, etc.

Art. 014-1087-000

Meclube-Lock display box
Composed bay:
30 pcs quick couplers Meclube-Lock length 32mm
Supplied in blister packaging


014-1087-000