



Meclube Model FOOD SS120

Made of electro-polished
SS AISI 316

Compression ratio:

1:1

Max flow-rate:

120 l/min

Fluid connections:

1.1/2" Tri-Clamp

FDA
compliant


EX II 3/3 GD h IIB T4 135 °C ATEX zone2

ARTICLE	CASING	DIAPHRAGM	BALLS	GASKET	FLUIDS
028-F120-AB1	SS AISI 316 E-P	NBR+PTFE	SS AISI 316	PTFE	high viscosity food products
028-F120-AB2	SS AISI 316 E-P	NBR+PTFE	PTFE	PTFE	low viscosity food and drink products

Technical data

Fluid connections:	1.1/2" Tri-Clamp
Air connection:	3/8" BSP
Max flow-rate:	120 l/min
Max air pressure:	8 bar
Max delivery head:	80 m
Max Suction Lift Dry:	5 m
Max Suction Lift Wet:	9,8 m
Max Solid passing:	4,0 mm
Noise level:	72 dB
Displacement per cycle:	200 cm³
Max Viscosity:	25000 cps

Performance



The curves and performance values refer to pumps with submerged suction and a free delivery outlet with water at 20 °C, and vary according to the construction material.

Dimensions

Food SS120

A (mm)	259
B (mm)	177
C (mm)	296
Gross weight kg	9,53
MAX Temperature	-20 °C + 95 °C

