

Battery electric vane self-priming pump 12 or 24V direct electricity, constituted by cast iron body, sintered steel impeller and acetyl resin vane. Built-in by-pass valve and stainless steel filter.



Battery electric pump 60 l for diesel transfer equipped with:

- Power cable 4 m length sec. 4 mmq with pincers and fuse
- Power cable 6 m length sec. 4 mmq with pincers and fuse
- Self-priming rotary electric pump
- Cast iron body
- By-pass valve
- DC Engine
- Stainless steel filter 100 micron
- Motor protection rating IP55
- Max by-pass valve pressure 1,5 bar

Ref.	Flow rate	Voltage	Power	Electricity	Cable length	Inlet-Outlet	Duty cycle	Max suction height	Weight	Packaging
	l/min	DC Volt	W	A	m	BSPG	min	m	kg	mm

091-5081-060	60	12	336	19	4	F 1"-F 1"	40	3	6,80	245X180X190
091-5083-060	60	24	432	11	4	F 1"-F 1"	40	3	6,80	245X180X190

091-5084-060	60	12	336	19	6	F 1"-F 1"	40	3	7,10	245X180X190
091-5085-060	60	24	432	11	6	F 1"-F 1"	40	3	7,10	245X180X190

Dimensions:

