

Automatic dispensing nozzles composed by aluminium body. Equipped with a device that shuts off the flow automatically when the tank is full. Suitable for quick and safe refuel, provided with swivel connection.



**Art. 093-5221-080 Automatic nozzle "ZVA80"**

for diesel fuel transfer  
Flow rate 80 l/min  
Aluminium body  
Swivel connection F 1"



**Art. 093-5221-120 Automatic nozzle "ZVA120"**

for diesel fuel transfer  
Flow rate 120 l/min  
Aluminium body  
Swivel connection F 1"



**Art. 093-5222-280 Automatic nozzle "PA280"**

for diesel fuel transfer  
Flow rate 280 l/min  
Aluminium body  
Swivel connection F 1.1/2"

Ref.	Model	Fluid	Flow rate	Inlet	Weight	Ø End	Packaging
		tipo	l/min	BSPG	Kg	mm	mm

<b>093-5221-080</b>	ZVA80	Diesel	<b>80</b>	F 1"	1,20	24,80	400X175X57
---------------------	-------	--------	-----------	------	------	-------	------------

<b>093-5221-120</b>	ZVA120	Diesel	<b>120</b>	F 1"	1,65	31,00	400X175X57
---------------------	--------	--------	------------	------	------	-------	------------

<b>093-5222-280</b>	PA280	Diesel	<b>280</b>	F 1.1/2"	2,20	39,50	420x220x573
---------------------	-------	--------	------------	----------	------	-------	-------------