

# TUBI IN DOTAZIONE AGLI AVVOLGITUBO

## ARIA-ACQUA da 20 a 28 bar

- Tubi in gomma sintetica nera R6
- Raccordi in acciaio zincato



| Articolo     | L.tubo | Ø Tubo-dimensioni | Pressione max | Entrata - Uscita    |
|--------------|--------|-------------------|---------------|---------------------|
| 902-0808-150 | 15 m   | 1.1/2"- 38X50 mm  | 20 bar        | F1.1/2"G - M1.1/2"G |
| 902-0808-200 | 20 m   | 1.1/2"- 38X50 mm  | 20 bar        | F1.1/2"G - M1.1/2"G |
| 902-0808-300 | 30 m   | 1.1/2"- 38X50 mm  | 20 bar        | F1.1/2"G - M1.1/2"G |
| 902-0909-150 | 15 m   | 2"- 51X66 mm      | 20 bar        | F2"G - M2"G         |
| 902-0909-200 | 20 m   | 2"- 51X66 mm      | 20 bar        | F2"G - M2"G         |
| 902-0909-300 | 30 m   | 2"- 51X66 mm      | 20 bar        | F2"G - M2"G         |

## ACQUA 150° C 200 bar

- Tubi in gomma sintetica blu antimacchia 1SC
- Raccordi in acciaio zincato
- Manopola in gomma blu



| Articolo     | L.tubo | Ø Tubo-dimensioni  | Pressione max | Entrata - Uscita |
|--------------|--------|--------------------|---------------|------------------|
| 904-0223-100 | 10 m   | 5/16"- 7,9X13,5 mm | 200 bar       | F3/8"G - F3/8"G  |
| 904-0223-150 | 15 m   | 5/16"- 7,9X13,5 mm | 200 bar       | F3/8"G - F3/8"G  |
| 904-0223-200 | 20 m   | 5/16"- 7,9X13,5 mm | 200 bar       | F3/8"G - F3/8"G  |
| 904-0323-100 | 10 m   | 3/8"- 9,5X15,6 mm  | 200 bar       | F3/8"G - F3/8"G  |
| 904-0323-150 | 15 m   | 3/8"- 9,5X15,6 mm  | 200 bar       | F3/8"G - F3/8"G  |
| 904-0323-180 | 18 m   | 3/8"- 9,5X15,6 mm  | 200 bar       | F3/8"G - F3/8"G  |
| 904-0323-200 | 20 m   | 3/8"- 9,5X15,6 mm  | 200 bar       | F3/8"G - F3/8"G  |
| 904-0323-250 | 25 m   | 3/8"- 9,5X15,6 mm  | 200 bar       | F3/8"G - F3/8"G  |
| 904-0323-300 | 30 m   | 3/8"- 9,5X15,6 mm  | 200 bar       | F3/8"G - F3/8"G  |
| 904-0323-400 | 40 m   | 3/8"- 9,5X15,6 mm  | 200 bar       | F3/8"G - F3/8"G  |
| 904-0323-500 | 50 m   | 3/8"- 9,5X15,6 mm  | 200 bar       | F3/8"G - F3/8"G  |
| 904-0424-100 | 10 m   | 1/2"- 12,8X19,1 mm | 200 bar       | F1/2"G - F1/2"G  |
| 904-0424-150 | 15 m   | 1/2"- 12,8X19,1 mm | 200 bar       | F1/2"G - F1/2"G  |
| 904-0424-200 | 20 m   | 1/2"- 12,8X19,1 mm | 200 bar       | F1/2"G - F1/2"G  |
| 904-0424-250 | 25 m   | 1/2"- 12,8X19,1 mm | 200 bar       | F1/2"G - F1/2"G  |
| 904-0424-300 | 30 m   | 1/2"- 12,8X19,1 mm | 200 bar       | F1/2"G - F1/2"G  |
| 904-0424-400 | 40 m   | 1/2"- 12,8X19,1 mm | 200 bar       | F1/2"G - F1/2"G  |

## ACQUA 150° C 400 bar

- Tubi in gomma sintetica blu antimacchia 2SC
- Raccordi in acciaio zincato
- Manopola in gomma blu



| Articolo     | L.tubo | Ø Tubo-dimensioni | Pressione max | Entrata - Uscita |
|--------------|--------|-------------------|---------------|------------------|
| 905-0223-100 | 10 m   | 5/16"- 7,9X15 mm  | 400 bar       | F3/8"G - F3/8"G  |
| 905-0223-150 | 15 m   | 5/16"- 7,9X15 mm  | 400 bar       | F3/8"G - F3/8"G  |
| 905-0223-200 | 20 m   | 5/16"- 7,9X15 mm  | 400 bar       | F3/8"G - F3/8"G  |
| 905-0323-100 | 10 m   | 3/8"- 9,5X17 mm   | 400 bar       | F3/8"G - F3/8"G  |
| 905-0323-150 | 15 m   | 3/8"- 9,5X17 mm   | 400 bar       | F3/8"G - F3/8"G  |
| 905-0323-180 | 18 m   | 3/8"- 9,5X17 mm   | 400 bar       | F3/8"G - F3/8"G  |
| 905-0323-200 | 20 m   | 3/8"- 9,5X17 mm   | 400 bar       | F3/8"G - F3/8"G  |
| 905-0323-250 | 25 m   | 3/8"- 9,5X17 mm   | 400 bar       | F3/8"G - F3/8"G  |
| 905-0323-300 | 30 m   | 3/8"- 9,5X17 mm   | 400 bar       | F3/8"G - F3/8"G  |
| 905-0323-400 | 40 m   | 3/8"- 9,5X17 mm   | 400 bar       | F3/8"G - F3/8"G  |
| 905-0323-500 | 50 m   | 3/8"- 9,5X17 mm   | 400 bar       | F3/8"G - F3/8"G  |