

TUBI COLLEGAMENTO PER AVVOLGITUBO

ACQUA 150° C 200 bar

- Tubi in gomma sintetica blu antimacchia 1SC
- Raccordi in acciaio zincato

Articolo	L.tubo	Ø Tubo-dimensioni	Pressione max	Entrata - Uscita
904-0323-006	0,6 m	3/8" - 9,5X15,6 mm	200 bar	F3/8"G - F3/8"G
904-0323-015	1,5 m	3/8" - 9,5X15,6 mm	200 bar	F3/8"G - F3/8"G
904-0424-006	0,6 m	1/2" - 12,8X19,1 mm	200 bar	F1/2"G - F1/2"G
904-0424-015	1,5 m	1/2" - 12,8X19,1 mm	200 bar	F1/2"G - F1/2"G



ACQUA 150° C 400 bar

- Tubi in gomma sintetica blu antimacchia 2SC
- Raccordi in acciaio zincato

Articolo	L.tubo	Ø Tubo-dimensioni	Pressione max	Entrata - Uscita
905-0323-006	0,6 m	3/8" - 9,5X17,0 mm	400 bar	F3/8"G - F3/8"G
905-0323-015	1,5 m	3/8" - 9,5X17,0 mm	400 bar	F3/8"G - F3/8"G
905-0424-006	0,6 m	1/2" - 12,8X20,4 mm	400 bar	F1/2"G - F1/2"G
905-0424-015	1,5 m	1/2" - 12,8X20,4 mm	400 bar	F1/2"G - F1/2"G



OLIO E AFFINI da 88 a 160 bar

- Tubi in gomma sintetica nera 1SC
- Raccordi in acciaio zincato

Articolo	L.tubo	Ø Tubo-dimensioni	Pressione max	Entrata - Uscita
906-0424-006	0,6 m	1/2" - 12,8X19,1 mm	160 bar	F1/2"G - F1/2"G
906-0434-008	0,8 m	1/2" - 12,8X19,1 mm	160 bar	F90° 1/2"G - F1/2"G
906-0424-010	1,0 m	1/2" - 12,8X19,1 mm	160 bar	F1/2"G - F1/2"G
906-0424-015	1,5 m	1/2" - 12,8X19,1 mm	160 bar	F1/2"G - F1/2"G
906-0424-020	2,0 m	1/2" - 12,8X19,1 mm	160 bar	F1/2"G - F1/2"G
906-0525-006	0,6 m	3/4" - 19X26 mm	105 bar	F3/4"G - F3/4"G
906-0535-008	0,8 m	3/4" - 19X26 mm	105 bar	F90° 3/4"G - F3/4"G
906-0525-010	1,0 m	3/4" - 19X26 mm	105 bar	F3/4"G - F3/4"G
906-0525-015	1,5 m	3/4" - 19X26 mm	105 bar	F3/4"G - F3/4"G
906-0525-020	2,0 m	3/4" - 19X26 mm	105 bar	F3/4"G - F3/4"G
906-0626-006	0,6 m	1" - 25,4X33,4 mm	88 bar	F1"G - F1"G
906-0636-008	0,8 m	1" - 25,4X33,4 mm	88 bar	F90° 1"G - F1"G
906-0626-010	1,0 m	1" - 25,4X33,4 mm	88 bar	F1"G - F1"G
906-0626-015	1,5 m	1" - 25,4X33,4 mm	88 bar	F1"G - F1"G
906-0626-020	2,0 m	1" - 25,4X33,4 mm	88 bar	F1"G - F1"G



GRASSO da 275 a 400 bar

- Tubi in gomma sintetica nera 2SC
- Raccordi in acciaio zincato

Articolo	L.tubo	Ø Tubo-dimensioni	Pressione max	Entrata - Uscita
907-0122-006	0,6 m	1/4" - 6,4X13,3 mm	400 bar	F1/4"G - F1/4"G
907-0132-008	0,8 m	1/4" - 6,4X13,3 mm	400 bar	F90° 1/4"G - F1/4"G
907-0122-015	1,5 m	1/4" - 6,4X13,3 mm	400 bar	F1/4"G - F1/4"G
907-0102-015	1,5 m	1/4" - 6,4X13,3 mm	400 bar	M1/4"G - F1/4"G
907-0122-020	2,0 m	1/4" - 6,4X13,3 mm	400 bar	F1/4"G - F1/4"G
907-0323-006	0,6 m	3/8" - 9,5X17 mm	330 bar	F3/8"G - F3/8"G
907-0333-008	0,8 m	3/8" - 9,5X17 mm	330 bar	F90° 3/8"G - F3/8"G
907-0323-015	1,5 m	3/8" - 9,5X17 mm	330 bar	F3/8"G - F3/8"G
907-0323-020	2,0 m	3/8" - 9,5X17 mm	330 bar	F3/8"G - F3/8"G
907-0424-006	0,6 m	1/2" - 12,8X20,4 mm	275 bar	F1/2"G - F1/2"G
907-0434-008	0,8 m	1/2" - 12,8X20,4 mm	275 bar	F90° 1/2"G - F1/2"G
907-0424-015	1,5 m	1/2" - 12,8X20,4 mm	275 bar	F1/2"G - F1/2"G
907-0424-020	2,0 m	1/2" - 12,8X20,4 mm	275 bar	F1/2"G - F1/2"G

